



Barton Lube

TECHNICAL DATA SHEET

HD TURBO 15W-40

Mineral oil based
engine oil Product
code: M023

Product Description:

HD TURBO 15W-40 is a multigrade engine oil manufactured from highly refined, high viscosity index base oils and carefully balanced additives producing a high quality petrol and diesel engine oil. It offers excellent high temperature stability and stay in grade performance. The additives used reduce the unwanted gums and varnishes in cylinders, on pistons and in turbochargers.

Benefits:

- Excellent performance
- Protection against sludging
- Stay in grade performance
- Good anti wear properties

Applications:

HD TURBO 15W-40 is suitable for normally aspirated and turbo charged diesel engines and petrol engines in passenger cars, light and heavy commercials, buses, agricultural, plant and construction equipment. It is miscible with all synthetic and mineral based engine oils.

Product Specification:

API	SG/CF-4
Caterpillar	TO-2
CCMC	G3/PD-2
VW	505.00
MB	227.1
MAN	271
Allison	C3
Military Spec	Mil-L-2104E

Typical Test Data:

Specific Gravity @ 15.6°C	0.886
Kinematic Viscosity @ 100°C (cSt)	14.3
Kinematic Viscosity @ 40°C (cSt)	105.0
Viscosity Index	139
Flash Point COC (°C)	215
Pour Point (°C)	-29
TBN (mg KOH / g)	9.09

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.